



VISHAY INTERTECHNOLOGY, INC.

LOAD CELLS

# LOAD CELLS

Vishay Tedea-Huntleigh



PRODUCT OVERVIEW



# Load Cells

Vishay Tedea-Huntleigh



## Aluminum Single-Point Load Cells

Product	Features	Capacities
<b>1002</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP66</li><li>Platform size 200 x 200 mm</li></ul>	<b>0.5, 1, 2, 3, 5, 8, 15, 20 kg</b>
<b>1004</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP66</li><li>Certified to OIML 3000d</li><li>Platform size 200 x 200 mm</li></ul>	<b>0.2, 0.3, 0.6, 1.5, 3 kg</b>
<b>1006</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP66</li><li>Platform size 200 x 200 mm</li></ul>	<b>2, 3, 5 kg</b>
<b>1010/1015</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP65 (optional IP67)</li><li>Certified to NTEP 5000d</li><li>ATEX certified versions available for explosive atmosphere</li><li>Factory Mutual approved for intrinsic safety</li><li>Platform size 400 x 400 mm</li></ul>	<b>3, 5, 7, 10, 15, 20, 30, 50, 90 kg</b>
<b>1022</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP66</li><li>Certified to OIML 4000d</li><li>Certified to NTEP 5000d</li><li>ATEX certified versions available for explosive atmosphere</li><li>Factory Mutual approved for intrinsic safety</li><li>Platform size 350 x 350 mm</li></ul>	<b>3, 5, 7, 10, 15, 20, 30, 35, 50, 100, 150, 200 kg</b>
<b>1030</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP65 (optional IP67)</li><li>Certified to OIML 2500d</li><li>ATEX certified versions available for explosive atmosphere</li><li>Factory Mutual approved for intrinsic safety</li><li>Platform size 350 x 350 mm</li></ul>	<b>2, 3, 5, 7, 10, 15 kg</b>
<b>1040</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP65 (optional IP67)</li><li>Certified to OIML 3000d</li><li>Certified to NTEP 5000d</li><li>ATEX certified versions available for explosive atmosphere</li><li>Factory Mutual approved for intrinsic safety</li><li>Platform size 400 x 400 mm</li></ul>	<b>5, 7, 10, 15, 20, 30, 50, 75, 100 kg</b>
<b>1042</b> 	<ul style="list-style-type: none"><li>Anodized aluminum construction</li><li>Environmental sealed IP66</li><li>Certified to OIML 6000d</li><li>Certified to NTEP 5000d</li><li>ATEX certified versions available for explosive atmosphere</li><li>Factory Mutual approved for intrinsic safety</li><li>Platform size 400 x 400 mm</li></ul>	<b>1, 3, 5, 7, 10, 15, 20, 30, 50, 75, 100, 150, 250 kg</b>



## Aluminum Single-Point Load Cells (cont.)

Product	Features	Capacities
<b>1242</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 6000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 400 x 400 mm</li> </ul>	<b>50, 100, 150, 200, 250 kg</b>
<b>1250</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP65 (optional IP67)</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 800 x 800 mm</li> </ul>	<b>50, 75, 100, 150, 200, 250, 300, 500, 635, 750, 1000, 1500 kg</b>
<b>1252</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 600 x 600 mm</li> </ul>	<b>75, 100, 150, 200, 250, 300, 500, 635 kg</b>
<b>1260</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 600 x 600 mm</li> </ul>	<b>50, 75, 100, 150, 250, 300, 500, 635, 660 kg</b>
<b>1263</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Platform size 600 x 600 mm</li> </ul>	<b>50, 75, 100, 150, 200, 250, 300, 500, 635 kg</b>
<b>1265</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 6000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Platform size 800 x 800 mm</li> </ul>	<b>100, 150, 200, 250, 300, 500, 635, 660 kg</b>
<b>1320</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 3000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 1200 x 1200 mm</li> </ul>	<b>1000, 1500, 2000 kg</b>
<b>1330</b> 	<ul style="list-style-type: none"> <li>Anodized aluminum construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Platform size 800 x 800 mm</li> </ul>	<b>500, 750, 1000 kg</b>



## Stainless Steel Single Point

Product	Features	Capacities
<b>1130</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 6000d</li> <li>Certified to NTEP 4000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 400 x 400 mm</li> </ul>	<b>7, 10, 15, 20, 30, 50, 75, 100 kg</b>
<b>1140</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Environmental sealed IP65 (optional IP67)</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 400 x 400 mm</li> </ul>	<b>15, 20, 30, 50, 75, 100, 150 kg</b>
<b>1142</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Platform size 400 x 400 mm</li> </ul>	<b>10, 15, 20, 30, 50, 75, 100, 150 kg</b>
<b>1510</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Hermetically sealed IP68</li> <li>Certified to OIML 4000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> <li>Platform size 600 x 600 mm</li> </ul>	<b>100, 250, 500 kg</b>

## Beam Load Cells

Product	Features	Capacities
<b>355</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Hermetically sealed IP68</li> <li>Certified to OIML 4000d</li> <li>Certified to NTEP 4000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	<b>5, 10, 20, 30, 50, 100, 200, 250, 500 kg</b>
<b>3410/3420</b> 	<ul style="list-style-type: none"> <li>Nickel plated steel construction</li> <li>Environmental sealed IP67</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	<b>250, 500, 1000, 2000 kg  1000, 1500, 2500, 4000, 5000, 7500, 10000 lb</b>
<b>3520</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Environmental sealed IP67</li> <li>Certified to OIML 6000d</li> <li>ATEX certified versions available for explosive atmosphere</li> </ul>	<b>500, 1000, 2000 kg</b>
<b>3510</b> 	<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Hermetically sealed IP68</li> <li>Certified to OIML 6000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	<b>300, 500, 750, 1000, 1200, 2000, 3000, 5000 kg  1000, 1500, 2500, 4000 lb</b>
<b>4158</b> 	<ul style="list-style-type: none"> <li>Nickel plated steel construction</li> <li>Environmental sealed IP67</li> <li>Certified to NTEP 10000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	<b>10, 20, 25, 40, 50, 60, 75 klb</b>



<b>Damped Load Cells</b>			
Product	Image	Features	Capacities
240		<ul style="list-style-type: none"> <li>Epoxy painted steel enclosure / stainless steel enclosure</li> <li>Environmental sealed IP66</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> </ul>	2, 3, 5, 7, 10, 15, 20, 30, 50 kg
240D		<ul style="list-style-type: none"> <li>Epoxy painted steel enclosure / stainless steel enclosure</li> <li>Environmental sealed IP66</li> <li>Digital load cell</li> <li>RS232 / RS485 output with MOD BUD</li> </ul>	2, 3, 5, 7, 10, 15, 20, 30, 50 kg
9010		<ul style="list-style-type: none"> <li>Electroless nickel plated enclosure / stainless steel enclosure</li> <li>Environmental sealed IP65</li> <li>Unique tare load canceling mechanism</li> </ul>	3, 5, 7, 10, 15, 20, 30, 50, 90 kg
9010D		<ul style="list-style-type: none"> <li>Electroless nickel plated enclosure / stainless steel enclosure</li> <li>Environmental sealed IP65</li> <li>Unique tare load canceling mechanism</li> <li>Digital load cell</li> <li>RS232 / RS485 output with MOD BUD</li> </ul>	3, 5, 7, 10, 15, 20, 30, 50, 90 kg
<b>Compression Load Cells</b>			
Product	Image	Features	Capacities
120/122		<ul style="list-style-type: none"> <li>Stainless steel enclosure</li> <li>Hermetically sealed IP68</li> <li>ATEX certified versions available for explosive atmosphere</li> </ul>	5, 10, 20, 30, 50, 100, 150 t
220		<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Hermetically sealed IP68</li> <li>Certified to OIML 4000d</li> <li>Certified to NTEP 10000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	5, 10, 20, 30, 50 t
<b>Universal Load Cells</b>			
Product	Image	Features	Capacities
614		<ul style="list-style-type: none"> <li>Aluminum construction</li> <li>Environmental sealed IP67</li> <li>Certified to OIML 3000d</li> <li>ATEX certified versions available for explosive atmosphere</li> </ul>	50, 100, 150, 200, 300, 500 kg
615/616		<ul style="list-style-type: none"> <li>Nickel plated construction / stainless steel construction</li> <li>Environmental sealed IP67</li> <li>ATEX certified versions available for explosive atmosphere</li> </ul>	50, 100, 150, 200, 300, 500, 750, 1000 kg
619		<ul style="list-style-type: none"> <li>Nickel plated construction</li> <li>Environmental sealed IP67</li> <li>ATEX certified versions available for explosive atmosphere</li> </ul>	1.5, 2, 3, 5 t
620		<ul style="list-style-type: none"> <li>Stainless steel construction</li> <li>Hermetically sealed IP68</li> <li>Certified to OIML 3000d</li> <li>Certified to NTEP 5000d</li> <li>ATEX certified versions available for explosive atmosphere</li> <li>Factory Mutual approved for intrinsic safety</li> </ul>	0.5, 1, 2, 5 t

**NOTICE** Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies. Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right. The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.



**VISHAY MEASUREMENTS GROUP:**

Vishay Micro-Measurements  
Vishay Transducers  
Vishay Systems—Weighing and Force Measurements



One of the World's Largest  
**Manufacturers**  
of Discrete Semiconductors and Passive Components

WORLDWIDE SALES CONTACTS

**THE AMERICAS**

**UNITED STATES**

VISHAY TRANSDUCERS AMERICAS  
801 SENTOUS AVENUE  
CITY OF INDUSTRY, CA 91748  
UNITED STATES  
PH: +1-800-872-4784 (TOLL FREE\*)  
+1-626-363-7500  
FAX: +1-626-332-3418  
E-MAIL: VT.US@VISHAYMG.COM  
\*US ONLY, OUTSIDE CALIFORNIA

**ASIA**

**TAIWAN, R.O.C.**

VISHAY TRANSDUCERS TAIWAN\*  
15 FL, NO. 86, SEC.1 SHINTAI 5TH RD.  
SIJHIH CITY, TAIPEI, 22102  
TAIWAN, R.O.C.  
PH: +886-2-2696-0168  
FAX: +886-2-2696-4965  
E-MAIL: VT.ROC@VISHAYMG.COM  
\*ASIA EXCEPT P.R. CHINA

**P.R. CHINA**

VISHAY TRANSDUCERS CHINA  
NO. 5 BINGUAN NAN DAO YOUYI RD.  
HEXI DISTRICT  
CODE 300061, TIANJIN  
P.R. CHINA  
PH: +86-22-2835-3503  
FAX: +86-22-2835-7261  
E-MAIL: VT.PRC@VISHAYMG.COM

**EUROPE**

**UNITED KINGDOM**

VISHAY MEASUREMENTS GROUP UK  
STROUDLEY ROAD, BASINGSTOKE  
HAMPSHIRE RG24 8FW  
UNITED KINGDOM  
PH: +44-125-646-2131  
FAX: +44-125-647-1441  
E-MAIL: VT.UK@VISHAYMG.COM

**NETHERLANDS**

VISHAY TRANSDUCERS THE NETHERLANDS  
RAMSHOORN 7  
P.O. BOX 6909  
4802 HX BREDA  
THE NETHERLANDS  
PH: +31-76-548-0700  
FAX: +31-76-541-2854  
E-MAIL: VT.NL@VISHAYMG.COM

**GERMANY**

VISHAY MEASUREMENTS GROUP GERMANY  
TATSCHENWEG 1  
74078 HEILBRONN  
GERMANY  
PH: +49-7131-39099-0  
FAX: +49-7131-39099-229  
E-MAIL: VT.DE@VISHAYMG.COM

**ISRAEL**

VISHAY MEASUREMENTS GROUP ISRAEL  
8A HAZORAN STREET  
P.O. BOX 8381  
NETANYA 42506  
ISRAEL  
PH: +972-9-863-8888  
FAX: +972-9-863-8800  
E-MAIL: VT.IL@VISHAYMG.COM

**FRANCE**

VISHAY MEASUREMENTS GROUP FRANCE  
16 RUE FRANCIS VOVELLE  
28000 CHARTRES  
FRANCE  
PH: +33-2-37-33-31-20  
FAX: +33-2-37-33-31-29  
E-MAIL: VT.FR@VISHAYMG.COM

[www.vishaymg.com](http://www.vishaymg.com)

[www.vishay.com](http://www.vishay.com)